

Material Safety Data Sheet
Mulberry

QuestVapco Corporation
P.O. Box 624
Brenham, TX 77834
Emergency Phone Number: (800) 231-0454

DATE PREPARED: 01/04/2013
REVISION DATE: 04/24/2013
CHEM-TEL: 800-225-3924
PRODUCT NUMBER: 3360

SECTION I - IDENTIFICATION

PRODUCT NAME: Mulberry DAF
PRODUCT CODE: 3360
PRODUCT USE: Air Freshener

SECTION II – COMPOSITION/HAZARDOUS INGREDIENTS

HAZARDOUS INGREDIENT	CAS NUMBER	OSHA PEL	ACGIH TLV
Isoparaffinic Hydrocarbon	64742-47-8	400 ppm	400 ppm
Propane/N-Butane	68476-86-8	N/A	1000 ppm

SECTION III – HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW: Aerosol under pressure do not expose to high temperatures above 120°F or store in direct sunlight may develop pressure and cause can to burst.

ROUTES OF ENTRY: Eyes, Ingestion, Inhalation, Skin

EYES: May cause irritation.

INGESTION: May cause gastric discomfort and nausea. No hazard by this route in normal use.

INHALATION: No hazards under normal use due to its low volatility. If vapor is present in high concentrations, irritation to upper respiratory tract may occur.

SKIN: May cause irritation, localized defatting, dermatitis, with prolonged or repeated contact.

MEDICAL CONDITION AGGRAVATED: None known

CHRONIC HEALTH HAZARDS: None known

CARCINOGENICITY:

OSHA: No **ACGIH:** No **NTP:** No **IARC:** No **OTHER:** N/A

SECTION IV - FIRST AID MEASURES

EYES: Immediately flush with water for 15 - 20 minutes while holding eyelids open. Seek medical attention if irritation persists.

INGESTION: Do not induce vomiting unless directed by medical authority. Immediately rinse mouth with water. Drink large quantities (1 qt, 2-4 glasses) of warm water. Seek immediate medical attention.

INHALATION: Move to fresh air. If breathing is difficult or unconscious, administer oxygen. If not breathing administer artificial respiration. Seek medical attention if irritation persists.

SKIN: Immediately wash with soap and water for 15 minutes. Seek medical attention if irritation develops.

NOTE TO PHYSICIAN: None

SECTION V – FIRE-FIGHTING MEASURES

FLASH POINT: > 200°F

EXTINGUISHING MEDIA: Dry chemical, carbon dioxide, foam, and water spray or fog.

SPECIAL FIRE FIGHTING PROCEDURES: Wear NIOSH approved Self Contained Breathing Apparatus with a full face piece operated in a positive pressure demand mode with full body protective clothing when fighting fires. Avoid breathing smoke, fumes, and decomposition products. Cool fire exposed containers with water fog to prevent bursting.

UNUSUAL FIRE AND EXPLOSION HAZARDS: FLAMMABLE. Contents under pressure. Exposure to temperatures above 120°F may cause bursting. Keep away from heat, sparks, open flames and other sources of ignition. Cool containers with water spray.

HAZARDOUS COMBUSTION PRODUCTS: Oxides of carbon

Material Safety Data Sheet
Mulberry

SECTION VI – ACCIDENTAL RELEASE MEASURES

SPILL: Stop all leaks, isolate hazard area, absorb spill with inert material (dry sand, dirt, etc) eliminate all ignition sources. prevent runoff from entering drain, sewers, streams, and other bodies of water.
WASTE DISPOSAL: Dispose of in accordance with federal, state, and local regulations. Do not dump in sewers. Wrap container and place in trash collection, do not puncture, incinerate, or reuse container.
RCRA STATUS: Waste likely considered non-hazardous under RCRA, however product should be fully characterized prior to disposal (40 CFR 261).

SECTION VII – HANDLING AND STORAGE

HANDLING AND STORAGE: Store in a cool dry area. Do not use or store near heat or open flame. Exposure to temperatures above 120F may cause bursting. Do not puncture or incinerate container. Do not reuse empty container. Wrap container and place in trash collection.
OTHER PRECAUTIONS: Keep out of the reach of children. Follow label directions exactly.

SECTION VIII – EXPOSURE CONTROLS/PERSONAL PROTECTION

ENGINEERING CONTROLS / VENTILATION: Ambient ventilation adequate.
RESPIRATORY PROTECTION: Not required with normal use.
PROTECTIVE CLOTHING: Safety glasses and chemical resistant gloves are recommended.
ADDITIONAL MEASURES: Wash hands thoroughly after use.

SECTION IX - PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE: White liquid
ODOR: Mulberry scent
PHYSICAL STATE: Liquid
VAPOR PRESSURE (mm Hg): 17.5 @ 77°F (25°C)
VAPOR DENSITY (AIR=1): > 1
EVAPORATION RATE: < 1
SPECIFIC GRAVITY (H2O=1): 0.98
pH: 7.0
SOLUBILITY IN WATER: 63%
VOLATILE ORGANIC COMPOUNDS (VOC): 25%

SECTION X – STABILITY AND REACTIVITY DATA

CHEMICAL STABILITY: Stable
CONDITIONS TO AVOID: Temperatures greater than 120 F, excessive heat, hot surfaces. Dropping may cause bursting.
INCOMPATIBILITY: Strong oxidizers, Alkalies, Acids
HAZARDOUS DECOMPOSITION OR BY-PRODUCT: Oxides of carbon
HAZARDOUS POLYMERIZATION: Will not occur

SECTION XI – TOXICOLOGICAL INFORMATION

TOXICOLOGICAL INFORMATION: Isoparaffinic Hydrocarbon - 64742-47-8: Oral rat LD50: 5 g/kg; Skin rabbit LD50: 2 g/kg; Inhalation rat LC50: 5 mg/L (4-hr)

SECTION XII – ECOLOGICAL INFORMATION

ECOLOGICAL INFORMATION: **Distillates, Petroleum, Hydrotreated, Lights** (64742-47-8) Not expected to be harmful or demonstrate chronic toxicity toward aquatic organisms. Biodegradation: Expected to be readily biodegradable. Hydrolysis: Transformation due to hydrolysis not expected to be significant. Photolysis: Transformation due to photolysis not expected to be significant. Atmospheric Oxidation: Expected to degrade rapidly in air.

Material Safety Data Sheet
Mulberry

SECTION XIII – DISPOSAL CONSIDERATIONS

WASTE DISPOSAL: Dispose of in accordance with federal, state, and local regulations. Do not dump in sewers. Wrap container and place in trash collection, do not puncture, incinerate, or reuse container.

RCRA STATUS: Waste likely considered non-hazardous under RCRA, however product should be fully characterized prior to disposal (40 CFR 261).

SECTION XIV - TRANSPORTATION INFORMATION

PROPER SHIPPING NAME: ORM-D

AIR SHIPMENT

PROPER SHIPPING NAME: Aerosols, Ltd. Qty. Class 2

HAZARD CLASS/DIVISION: 2.2

UN/NA NUMBER: UN 1950

PACKAGING GROUP: N/A

SHIPPING BY WATER:

VESSEL (IMO/IMDG)

PROPER SHIPPING NAME: Aerosols, Ltd. Qty. Class 2

HAZARD CLASS/DIVISION: 2.2

UN/NA NUMBER: UN 1950

PACKAGING GROUP: N/A

NOTE:

SECTION XV - REGULATORY INFORMATION

TSCA STATUS: All Chemicals are listed or exempt.

CERCLA (COMPREHENSIVE RESPONSE COMPENSATION, AND LIABILITY ACT): None

SARA 311/312 HAZARD CATEGORIES: None

SARA 313 REPORTABLE INGREDIENTS: None

STATE REGULATIONS: California Proposition 65: None

INTERNATIONAL REGULATIONS: Distillates, Petroleum, Hydrotreated, Lights (64742-47-8)

NFPA HEALTH: 1

HMIS HEALTH: 1

NFPA FLAMMABILITY: 1

HMIS FLAMMABILITY: 1

NFPA REACTIVITY: 0

HMIS REACTIVITY: 0

NFPA OTHER: N/A

HMIS PROTECTION: A

SECTION XVI - ADDITIONAL INFORMATION

PREPARATION BY: John Holdren

DISCLAIMER: To the best of our knowledge, information contained herein is accurate. However there is no assumption of liability for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazard which exists. The information contained in this MSDS was obtained from current and reliable sources; however, the data is provided without any warranty, expressed or implied, regarding its correctness or accuracy. Since the conditions or handling, storage and disposal of this product are beyond the control of the manufacturer, the manufacturer will not be responsible for loss, injury, or expense arising out of the products improper use. No warranty, expressed or inferred, regarding the product described in this MSDS shall be created or inferred by any statement in this MSDS. Various government agencies may have specific regulations regarding the transportation, handling, storage, use, or disposal of this product which may not be covered by this MSDS. The user is responsible for full compliance.